



Acoustic cabinet fans **CVAB / CVAT Series**

**CVAT/4 1200/250 *400V*
50Hz VE**



Range of in-line cabinet fans, manufactured from galvanised steel sheet with double thickness side panels internally lined with 17 mm thickness of fireproof fibreglass acoustic insulation (M0). All models incorporate backward curved centrifugal impellers, dynamically balanced and are supplied with circular duct connection flanges and remote terminal box. Available, depending upon the model, with single phase or three phase motors in 4 or 6 poles.

Motors

All the motors are IP55, Class F(1) insulation, with thermal protection (2).

Electrical supply:

Single phase 230V-50Hz.

Three phase 230/400V-50Hz.

(See characteristics chart).

Three phase motors are speed controllable by inverter.

(1)


Air stream temperature limits -40°C to +70°C.

Models /4-9000 and /6-6000 to /6-17000 suitable for usage in environments up to +40°C).

(2)

Except models 6000 to 17000.

+ Attributes



Backward curved centrifugal impellers To prevent accumulation of dirtiness. Dynamically balanced.



Low noise level
Double thickness side panels internally lined with 17 mm thickness of fireproof fibreglass acoustic insulation (M0), to reduce significantly the radiated noise.



Cabinet air tightness
All models incorporate inlet and discharge circular duct connection flanges with integrated rubber air seal.



Robustness
Quality finished aluminium duct corners providing a great robustness.



Anti-vibration mounts
To reduce vibration and noise transmissions to the installation.

+ Acoustic characteristics

Unfortunately an error occurred.

+ Technical characteristics


Unfortunately an error occurred.

+ Dimensions

Unfortunately an error occurred.


11

+ Curves



+ Configuration

Configuración versátil



+ Mounting Accessories



MBE
Electric heaters.



MBW
Hot water coil.



MFL-G4
Filtration boxes.




SIL
Sound attenuators.



ACOPEL F400 N
Circular flexible connector.



CRC
Circular reducers.



APC
Discharge protection guards for direct connection to the inlet-outlet flange (for more information see Mounting accessories).



CTI CVA
Outdoor cover
For outdoor installations.

+ Electrical Accessories



REB
Single phase electronic speed controllers.



REB-5
Single phase electronic speed controllers.



RMB/RMT
Single and three phase auto transformer speed controllers.



ON/OFF ELECTRICAL ISOLATION SWITCH
- Switch ON/OFF 5P
- Switch ON/OFF 8P



TG-K330
Duct temperature sensor.



PULSER
Single phase/three phase electric heater controller.



TTC-2000
TTC-2000 + TTS-1
Three phase electric heater controller.
The TTC-2000 needs an external temperature sensor to control the heater (TG-K300 or TG-R530).



VFTM IP54
Adjustable frequency drives for three phase motors from 0,37 to 15 kW.



VFKB IP65
Adjustable frequency drive for three phase motors from 0,37 to 4 kW.